



# Material Safety Data Sheet

<b>Revision Date</b> February 7 <sup>th</sup> , 2005	<b>Prepared by</b> David MacKinnon	<b>Technical Information</b> 1-800-201-8822 or <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>
<b>Head Office</b> 9347 - 193 Street, Surrey, B.C., V4N 4E7		<b>Emergency</b> Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from [www.mgchemicals.com](http://www.mgchemicals.com) or fax requests to 1-800-708-9888

## Section 1: Product Identification

**MSDS Code: 8332 - Part B**      **Name: Fast Setting Epoxy Adhesive**

**Related Part Numbers: 8332-25ML**

Use: A fast setting epoxy adhesive.

## Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
*proprietary proprietary registration # 679485-6533P	mercaptan amine blend	90 - 100	n/e	n/e	n/e

## Section 3: Hazards Identification

**WHMIS Codes:** D2B

**NFPA Ratings:** Health 3 Flammability 1 Reactivity 1

**HMIS Ratings:** Health 3 Flammability 1 Reactivity 1

**Eyes:** Causes severe irritation with possible permanent damage and even blindness.

**Skin:** Can cause severe irritation, especially on prolonged contact. Potential sensitizer.

**Inhalation:** Considered slightly toxic. Can cause irritation of respiratory tract. Over exposure to fumes or vapors may cause delayed lung and chemical pneumonia.

**Ingestion:** Slightly toxic. May cause fatigue, muscle weakness, gastrointestinal irritation, nausea, vomiting and diarrhea.

**Chronic:** Prolonged or repeated skin contact may cause sensitization, with itching, swelling, or rashes on later exposure.

## Section 4: First Aid Measure

**Eyes:** Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid if symptoms persist.

**Skin:** Wash skin with large quantities of soap and water. Get medical aid if symptoms persist.

**Inhalation:** Immediately remove from exposure to fresh air. Get medical aid if symptoms persist.

**Ingestion:** Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

## Section 5: Fire Fighting Measures

**Autoignition** n/e

**Flash Point:** >93°C

**LEL / UEL:** n/e



**Temperature:**

**Extinguishing Media:** Use water, dry chemical, carbon dioxide, or chemical foam.

**General Information:** Firefighters should wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers with water.

### Section 6: Accidental Release Measures

**Spill Procedure:** Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection. Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water.

### Section 7: Handling and Storage

**Handling:** Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do not expose container to heat or flame.

**Storage:** Keep away from sources of ignition. Store in a cool, dry, well ventilated area, away from incompatible substances.

### Section 8: Exposure Controls

**Routes of entry:** Eyes, ingestion, inhalation, and skin.

**Ventilation:** Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

**Personal Protection:** Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

### Section 9: Physical and Chemical Properties

<b>Physical State:</b>	liquid	<b>Odor:</b>	odorless	<b>Solubility:</b>	none	<b>Evaporation Rate:</b>	n/d
<b>Boiling Point:</b>	n/e	<b>Specific Gravity:</b>	1.13	<b>Vapor Pressure:</b>	<<0.02psi @21°C	<b>Vapor Density:</b>	>1 (Air=1) <b>pH:</b> 9.5

### Section 10: Stability and Reactivity

**Stability:** Stable at normal temperatures and pressures.

**Conditions to avoid:** n/a

**Incompatibilities:** Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases, especially primary and secondary aliphatic amines.

**Polymerization:** Heat is generated when hardner is mixed with epoxy resins.

**Decomposition:** Carbon dioxide, and carbon monoxide, nitrogen oxides.

### Section 11: Toxicological Information

**Sensitization:** (effects of repeated exposure) This product is a skin sensitizer.

**Carcinogenicity:** (risk of cancer) No

**Teratogenicity:** (risk of malformation in an unborn fetus) No





This product does not contain any ozone depleting substances.

**Industry and Science Canada**

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

**RoHS** (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

**Section 16: Other Information**

**Definitions:** n/a = not applicable, n/e = not established

**Disclaimer:** This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.